

THE BRIGANTIA ARCHAEOLOGICAL PRACTICE

BRITANNIA CHAMBERS
18A HORSEMARKET
BARNARD CASTLE
COUNTY DURHAM DL12 8LZ

1/15/293/PA



Telephone/Fax Teesdale (01833) 630125

Gail Falkingham,
Heritage Unit,
North Yorkshire County Council,
County Hall,
Northallerton DL7 8AQ.

NYCC HER	
SNY	675
ENY	308
CNY	1777
Parish	1015
Rec'd	14/07/1999

13, vii, 1999

Dear Gail,

WATCHING BRIEF AT ALLEN HOUSE, CATTERICK VILLAGE

This is to inform you that I attended on Friday, 9th of July, to carry out a watching brief during the stripping of the above site, on instructions from The Plan Shop, Bedale and according to a standard specification from NYCC. I enclose a site location plan, and a detailed drawing to show the excavated area.

The site was entirely covered by a modern garden soil (including some modern rubble towards the north), of an average 35 cms. depth. At the limit of excavation, this came down onto the upper surface of the natural subsoil, at this point a hard, sandy gravel. Nowhere was there any trace of any early feature, deposit or structure. A close watch maintained during stripping failed to reveal any loose find of a date earlier than the last century.

I trust that this information will allow discharge of my client's planning condition.


With best wishes,

423821 497982

Yours sincerely,

Percival Turnbull.

N	
ENVIRON	
Recd.	14 JUL 1999
Pass to	JHE
Ackd.
Ansd.
.....	
.....	



Supply and lay new Hepsleve VCIC inspection chambers on the new foul drain as indicated, including raising pieces and alloy cover and frame.

Lay drains under concrete floor slab on 50mm bed of 10mm granular material to BS 882, cutting out for sockets, and surround pipes in to half pipe depth in similar material. Backfill trenches with selected spoil ensuring that there is a minimum of 300mm cover between the pipe and the underside of the slab. Where cover is less than 300mm, encase the pipe in 150mm concrete.

Existing manhole
Existing foul drain

Existing manhole

Existing drain to be cut back and sealed

AREA STRIPPED

Supply and lay new Hepsleve VCIC inspection chambers on the new foul drain as indicated, including raising pieces and alloy cover and frame.

Encase all drains with less than 900mm of cover in 150mm concrete with flexible joints to pipes maintained in accordance with Hepworth's recommendations. Backfill trenches

Supply and fix new Hepworth P trap

Drain
Sup
Surf
soak
and
BS

