
## **GEOPHYSICAL SURVEY REPORT**



## Lower Farm, Newbury, Berkshire

Client

**RPS** 

Survey Report

12028

Date

**November 2017** 

Incorporating

**GSB PROSPECTION LTD** 

and

STRATASCAN LTD

SUMO Services Ltd Cowburn Farm Market Street Thornton Bradford BD13 3HW T: 01274 835016 SUMO Services Ltd Vineyard House Upper Hook Road Upton upon Severn Worcestershire WR8 0SA T: 01684 592266

geophysics@sumoservices.com www.sumoservices.com Project Name: Lower Farm, Newbury, Berkshire

Job ref: 12028
Client: RPS

Date: Nov 2017

## **GEOPHYSICAL SURVEY REPORT**

Project name: SUMO Job reference:

Lower Farm, Newbury, Berkshire 12028

Client: RPS

Survey date: Report date:

3 November 2017 20 November 2017

Field co-ordinator: Field Team:

Stephen Weston BA Simon Lobel MSc

Report written by: CAD illustrations by: Rebecca Davies BSc Rebecca Davies BSc

Project Manager: Report approved by:

Simon Haddrell BEng AMBCS PCIfA Dr John Gater BSc DSc(Hon) MCIfA FSA

## **TABLE OF CONTENTS**

1	SUMMARY OF RESULTS	1
2	INTRODUCTION	1
3	METHODS, PROCESSING & PRESENTATION	2
4	RESULTS	3
5	DATA APPRAISAL & CONFIDENCE ASSESSMENT	3
6	CONCLUSION	4
7	REFERENCES	4
Appendix A Technical Information: Magnetometer Survey Method		

## **LIST OF FIGURES**

Appendix B

Figure 01	1:25 000	Site Location Diagram
Figure 02	1:1000	Location of Survey Area
Figure 03	1:1250	Magnetometer Survey - Greyscale Plots & Interpretation

**Technical Information: Magnetic Theory** 

# DIGITAL CONTENT (Archive Data CD/DVD)



- Minimally Processed Greyscale Images and XY Trace Plots in DWG format
- Digital Copies of Report Text and Figures (both PDF and native formats)

Job ref: 12028 Date: Nov 2017

#### 1 SUMMARY OF RESULTS

A detailed magnetometer survey was conducted over approximately 2.1 ha of pasture. No archaeological responses have been identified. A weak curvilinear trend is of uncertain origin, while the remaining responses are natural or modern, and include evidence of ploughing and disturbance from nearby ferrous metal objects.

#### 2 INTRODUCTION

#### 2.1 Background synopsis

**SUMO Services Ltd** were commissioned to undertake a geophysical survey of an area outlined for the development of holiday lodges, associated parking and landscaping. This survey forms part of an archaeological investigation being undertaken by **RPS**.

#### 2.2 Site details

NGR / Postcode SU 493 659 / RG19 8SP

**Location** The site is located to the south-east of Newbury, Berkshire. Newbury

Racecourse lies to the north-west of the area, with an area of rough pasture and a former gravel pit to the north and agricultural land to the

south and east.

HER/SMR West Berkshire
Unitary Authority West Berkshire
Parish Greenham CP

**Topography** Slight slope down from west to east

**Current Land Use** Pasture

Weather Sunny, some cloud, dry

**Geology** Solid: Lambeth Group – clay, silt and sand. Superficial: None recorded

(BGS 2017).

Soils Wickham 3 Association (711g) - fine loamy over clayey and coarse

loamy over clayey soils (SSEW 1983).

**Archaeology** An archaeological evaluation on land immediately to the north of the site

confirmed the presence of a ring ditch, though no evidence for an internal mound, external bank or burial were identified. Several prehistoric flint artefacts have been recovered from around Lower Farm, along with a

probable trackway (RPS 2017).

**Survey Methods** Magnetometer survey (fluxgate gradiometer)

Study Area 2.1 ha

#### 2.3 Aims and Objectives

To locate and characterise any anomalies of possible archaeological interest within the study area.

Job ref: 12028 Date: Nov 2017

## 3 METHODS, PROCESSING & PRESENTATION

## 3.1 Standards & Guidance

This report and all fieldwork have been conducted in accordance with the latest guidance documents issued by Historic England (EH 2008) (then English Heritage), the Chartered Institute for Archaeologists (ClfA 2014) and the European Archaeological Council (EAC 2016).

## 3.2 Survey methods

Detailed magnetic survey was chosen as an efficient and effective method of locating archaeological anomalies.

Technique	Instrument	Traverse Interval	Sample Interval
Magnetometer	Bartington Grad 601-2	1.0m	0.25m

More information regarding this technique is included in Appendix A.

## 3.3 Data Processing

The following basic processing steps have been carried out on the data used in this report:

De-stripe; de-stagger; interpolate

#### 3.4 Presentation of results and interpretation

The presentation of the results for each site involves a grey-scale plot of processed data. Magnetic anomalies are identified, interpreted and plotted onto the 'Interpretation' drawings. The minimally processed data are provided as a greyscale image in the Archive Data Folder with an XY trace plot in CAD format. A free viewer is available: <a href="https://viewer.autodesk.com">https://viewer.autodesk.com</a>

When interpreting the results, several factors are taken into consideration, including the nature of archaeological features being investigated and the local conditions at the site (geology, pedology, topography etc.). Anomalies are categorised by their potential origin. Where responses can be related to other existing evidence, the anomalies will be given specific categories, such as: *Abbey Wall* or *Roman Road*. Where the interpretation is based largely on the geophysical data, levels of confidence are implied, for example: *Probable*, or *Possible Archaeology*. The former is used for a confident interpretation, based on anomaly definition and/or other corroborative data such as cropmarks. Poor anomaly definition, a lack of clear patterns to the responses and an absence of other supporting data reduces confidence, hence the classification *Possible*.

#### 4 RESULTS

Specific anomalies have been given numerical labels [1] [2] which appear in the text below, as well as on the Interpretation Figure.

## 4.1 Probable / Possible Archaeology

4.1.1 No magnetic responses have been recorded that could be interpreted as being of archaeological interest.

#### 4.2 Uncertain

4.2.1 A weak, curvilinear trend [1] is visible in the east of the area and is of uncertain origin. It is possible that this is of archaeological origin, given the proximity of a known ring ditch and associated activity to the north (RPS 2017). However, the response is very weak, and may simply reflect a chance alignment of magnetic debris within the topsoil.

## 4.3 Agricultural – Ploughing

4.3.1 Weakly magnetic, parallel linear responses are visible in the east of the area and are a result of modern agricultural activity such as ploughing.

#### 4.4 Natural / Geological / Pedological / Topographic

4.4.1 Three small areas of enhanced magnetic response are present in the data. These are typical of natural magnetic variations detected over clay, silt and sand geologies.

#### 4.5 Ferrous / Magnetic Disturbance

- 4.5.1 An area of strong magnetic disturbance in the north along with areas of weaker disturbance across the south and west are likely to be of modern origin, associated with ferrous debris. The area in the north may be a result of made ground.
- 4.5.2 Ferrous responses close to boundaries are due to adjacent fences and gates. Smaller scale ferrous anomalies ("iron spikes") are present throughout the data and their form is best illustrated in the XY trace plots. These responses are characteristic of small pieces of ferrous debris (or brick / tile) in the topsoil and are commonly assigned a modern origin. Only the most prominent of these are highlighted on the interpretation diagram.

#### 5 DATA APPRAISAL & CONFIDENCE ASSESSMENT

5.1 Historic England guidelines (EH 2008) Table 4 states that the average magnetic response on clay, silt and sand can be variable. Given that only a single, tentative linear response has been detected, along with weak evidence of ploughing, it is possible that the underlying geology is not fully conducive to magnetic survey.

#### Job ref: 12028 Date: Nov 2017

## 6 CONCLUSION

6.1 The survey at Lower Farm has not revealed any definite archaeological responses. A weak curvilinear anomaly is of uncertain origin, though it probably reflects a chance alignment of magnetic debris. Evidence of modern ploughing is visible, along with areas of natural magnetic variation and disturbance from nearby ferrous objects.

## 7 REFERENCES

BGS 2017	British Geological Survey, Geology of Britain viewer [Accessed 20/11/2017] website: (http://www.bgs.ac.uk/opengeoscience/home.html?Accordion1=1#maps)
ClfA 2014	Standard and Guidance for Archaeological Geophysical Survey. Amended 2016. CIfA Guidance note. Chartered Institute for Archaeologists, Reading <a href="http://www.archaeologists.net/sites/default/files/CIfAS%26GGeophysics_2.pdf">http://www.archaeologists.net/sites/default/files/CIfAS%26GGeophysics_2.pdf</a>
EAC 2016	EAC Guidelines for the Use of Geophysics in Archaeology, European Archaeological Council, Guidelines 2.
EH 2008	Geophysical Survey in Archaeological Field Evaluation. English Heritage, Swindon <a href="https://content.historicengland.org.uk/images-books/publications/geophysical-survey-in-archaeological-field-evaluation/geophysics-guidelines.pdf/">https://content.historicengland.org.uk/images-books/publications/geophysical-survey-in-archaeological-field-evaluation/geophysics-guidelines.pdf/</a>
RPS 2017	Land at Lower Farm, Newbury, West Berkshire – Heritage Statement. RPS; unpublished report.
SSEW 1983	Soils of England and Wales. Sheet 6, South East England. Soil Survey of England and Wales, Harpenden.

## Appendix A - Technical Information: Magnetometer Survey Method

#### **Grid Positioning**

For hand held gradiometers the location of the survey grids has been plotted together with the referencing information. Grids were set out using a Trimble R8 Real Time Kinematic (RTK) VRS Now GNSS GPS system.

An RTK GPS (Real-time Kinematic Global Positioning System) can locate a point on the ground to a far greater accuracy than a standard GPS unit. A standard GPS suffers from errors created by satellite orbit errors, clock errors and atmospheric interference, resulting in an accuracy of 5m-10m. An RTK system uses a single base station receiver and a number of mobile units. The base station rebroadcasts the phase of the carrier it measured, and the mobile units compare their own phase measurements with those they received from the base station. This results in an accuracy of around 0.01m.

Technique	Instrument	Traverse Interval	Sample Interval
Magnetometer	Bartington Grad 601-2	1m	0.25m

#### Instrumentation: Bartington *Grad* 601-2

Bartington instruments operate in a gradiometer configuration which comprises fluxgate sensors mounted vertically, set 1.0m apart. The fluxgate gradiometer suppresses any diurnal or regional effects. The instruments are carried, or cart mounted, with the bottom sensor approximately 0.1-0.3m from the ground surface. At each survey station, the difference in the magnetic field between the two fluxgates is measured in nanoTesla (nT). The sensitivity of the instrument can be adjusted; for most archaeological surveys the most sensitive range (0.1nT) is used. Generally, features up to 1m deep may be detected by this method, though strongly magnetic objects may be visible at greater depths. The Bartington instrument can collect two lines of data per traverse with gradiometer units mounted laterally with a separation of 1.0m. The readings are logged consecutively into the data logger which in turn is daily down-loaded into a portable computer whilst on site. At the end of each site survey, data is transferred to the office for processing and presentation.

#### **Data Processing**

Zero Mean Traverse This process sets the background mean of each traverse within each grid to zero. The operation removes striping effects and edge discontinuities over the whole of the data set.

Step Correction (De-stagger)

When gradiometer data are collected in 'zig-zag' fashion, stepping errors can sometimes arise. These occur because of a slight difference in the speed of walking on the forward and reverse traverses. The result is a staggered effect in the data, which is particularly noticeable on linear anomalies. This process corrects these errors.

## **Display**

Greyscale/ Colourscale Plot This format divides a given range of readings into a set number of classes. Each class is represented by a specific shade of grey, the intensity increasing with value. All values above the given range are allocated the same shade (maximum intensity); similarly, all values below the given range are represented by the minimum intensity shade. Similar plots can be produced in colour, either using a wide range of colours or by selecting two or three colours to represent positive and negative values. The assigned range (plotting levels) can be adjusted to emphasise different anomalies in the data-set.

#### **Interpretation Categories**

In certain circumstances (usually when there is corroborative evidence from desk-based or excavation data) very specific interpretations can be assigned to magnetic anomalies (for example, Roman Road, Wall, etc.) and where appropriate, such interpretations will be applied. The list below outlines the generic categories commonly used in the interpretation of the results.

Archaeology / Probable Archaeology

This term is used when the form, nature and pattern of the responses are clearly or very probably archaeological and /or if corroborative evidence is available. These anomalies, whilst considered anthropogenic, could be of any age.

Possible Archaeology

These anomalies exhibit either weak signal strength and / or poor definition, or form incomplete archaeological patterns, thereby reducing the level of confidence in the interpretation. Although the archaeological interpretation is favoured, they may be the result of variable soil depth, plough damage or even aliasing as a result of data collection orientation.

Industrial / Burnt-Fired Strong magnetic anomalies that, due to their shape and form or the context in which they are found, suggest the presence of kilns, ovens, corn dryers, metalworking areas or hearths. It should be noted that in many instances modern ferrous material can produce similar magnetic anomalies.

Former Field & possible)

Anomalies that correspond to former boundaries indicated on historic mapping, or Boundary (probable which are clearly a continuation of existing land divisions. Possible denotes less confidence where the anomaly may not be shown on historic mapping but nevertheless the anomaly displays all the characteristics of a field boundary.

Ridge & Furrow Parallel linear anomalies whose broad spacing suggests ridge and furrow cultivation. In some cases, the response may be the result of more recent

agricultural activity.

**Agriculture** (ploughing) Parallel linear anomalies or trends with a narrower spacing, sometimes aligned with existing boundaries, indicating more recent cultivation regimes.

Land Drain Weakly magnetic linear anomalies, quite often appearing in series forming parallel and herringbone patterns. Smaller drains may lead and empty into larger diameter pipes, which in turn usually lead to local streams and ponds. These are indicative

of clay fired land drains.

Natural These responses form clear patterns in geographical zones where natural

variations are known to produce significant magnetic distortions.

Maanetic Disturbance Broad zones of strong dipolar anomalies, commonly found in places where modern ferrous or fired materials (e.g. brick rubble) are present. They are presumed to be

modern.

Service Magnetically strong anomalies, usually forming linear features are indicative of

ferrous pipes/cables. Sometimes other materials (e.g. pvc) or the fill of the trench can cause weaker magnetic responses which can be identified from their uniform

linearity.

**Ferrous** This type of response is associated with ferrous material and may result from small

> items in the topsoil, larger buried objects such as pipes, or above ground features such as fence lines or pylons. Ferrous responses are usually regarded as modern. Individual burnt stones, fired bricks or igneous rocks can produce responses

similar to ferrous material.

Uncertain Origin Anomalies which stand out from the background magnetic variation, yet whose

form and lack of patterning gives little clue as to their origin. Often the characteristics and distribution of the responses straddle the categories of *Possible* Archaeology / Natural or (in the case of linear responses) Possible Archaeology /

Agriculture; occasionally they are simply of an unusual form.

Where appropriate some anomalies will be further classified according to their form (positive or negative) and relative strength and coherence (trend: weak and poorly defined).

#### Appendix B - Technical Information: Magnetic Theory

Detailed magnetic survey can be used to effectively define areas of past human activity by mapping spatial variation and contrast in the magnetic properties of soil, subsoil and bedrock. Although the changes in the magnetic field resulting from differing features in the soil are usually weak, changes as small as 0.1 nanoTeslas (nT) in an overall field strength of 48,000 (nT), can be accurately detected.

Weakly magnetic iron minerals are always present within the soil and areas of enhancement relate to increases in *magnetic susceptibility* and permanently magnetised *thermoremanent* material.

Magnetic susceptibility relates to the induced magnetism of a material when in the presence of a magnetic field. This magnetism can be considered as effectively permanent as it exists within the Earth's magnetic field. Magnetic susceptibility can become enhanced due to burning and complex biological or fermentation processes.

Thermoremanence is a permanent magnetism acquired by iron minerals that, after heating to a specific temperature known as the Curie Point, are effectively demagnetised followed by re-magnetisation by the Earth's magnetic field on cooling. Thermoremanent archaeological features can include hearths and kilns; material such as brick and tile may be magnetised through the same process.

Silting and deliberate infilling of ditches and pits with magnetically enhanced soil creates a relative contrast against the much lower levels of magnetism within the subsoil into which the feature is cut. Systematic mapping of magnetic anomalies will produce linear and discrete areas of enhancement allowing assessment and characterisation of subsurface features. Material such as subsoil and non-magnetic bedrock used to create former earthworks and walls may be mapped as areas of lower enhancement compared to surrounding soils.

Magnetic survey is carried out using a fluxgate gradiometer which is a passive instrument consisting of two sensors mounted vertically 1m apart. The instrument is carried about 30cm above the ground surface and the top sensor measures the Earth's magnetic field whilst the lower sensor measures the same field but is also more affected by any localised buried feature. The difference between the two sensors will relate to the strength of a magnetic field created by this feature, if no field is present the difference will be close to zero as the magnetic field measured by both sensors will be the same.

Factors affecting the magnetic survey may include soil type, local geology, previous human activity and disturbance from modern services.








Site Location

Reproduced from Ordnance Survey's 1:25 000 map of 1998 with the permission of the controller of Her Majesty's Stationery Office.

Crown Copyright reserved.

Licence No: AL 50125A



Title:

Site Location Diagram


Client:

RPS


12028 - Lower Farm, Newbury, Berkshire

Scale: 0	metres	1000	F
	1:25000 @ A3		

Fig No: 01







- Laser Scanning
- ArchaeologicalGeophysicalMeasured BuildingTopographic

  - Utility Mapping