
GEOPHYSICAL SURVEY REPORT



Nova Scotia, Caister, Great Yarmouth, Norfolk

Client

Persimmon Homes

Survey Report 11741

Date

October 2017

Incorporating

GSB PROSPECTION LTD

and

STRATASCAN LTD

SUMO Services Ltd Cowburn Farm Market Street Thornton Bradford BD13 3HW T: 01274 835016 SUMO Services Ltd Vineyard House Upper Hook Road Upton upon Severn Worcestershire WR8 0SA T: 01684 592266

geophysics@sumoservices.com www.sumoservices.com

Job ref: 11741 Date: Oct 2017

GEOPHYSICAL SURVEY REPORT

Project name: SUMO Job reference:

Nova Scotia, Caister, 11741

Great Yarmouth, Norfolk

Client:

Persimmon Homes

Survey date: Report date: 21-25 August, 11-12 September 2017 5 October 2017

Field co-ordinator: Field Team:

Robert Knight BA Adam Clark BA

Report written by: CAD illustrations by: Rebecca Davies BSc Rebecca Davies BSc

Project Manager: Report approved by:

Simon Haddrell BEng AMBCS PCIfA Dr John Gater BSc DSc(Hon) MCIfA FSA

TABLE OF CONTENTS

1	SUMMARY OF RESULTS	1	
2	INTRODUCTION	1-2	
3	METHODS, PROCESSING & PRESENTATION	2	
4	RESULTS	3	
5	DATA APPRAISAL & CONFIDENCE ASSESSMENT	4	
6	S CONCLUSION 4		
7	REFERENCES 4		
Appendix A Technical Information: Magnetometer Survey Method			

Appendix B Technical Information: Magnetic Theory

LIST OF FIGURES

Figure 01	1:2500	Site Location Diagram & Location of Survey Areas
Figure 02	1:2500	Magnetometer Survey - Greyscale Plots &
		Interpretation - Overview
Figure 03	1:1250	Magnetometer Survey - Greyscale Plots &
		Interpretation - North
Figure 04	1:1250	Magnetometer Survey - Greyscale Plots &
		Interpretation - South

DIGITAL CONTENT (Archive Data CD/DVD)



- Minimally Processed Greyscale Images and XY Trace Plots in DWG format
- Digital Copies of Report Text and Figures (both PDF and native formats)

1 SUMMARY OF RESULTS

A detailed magnetometer survey was conducted over approximately 30ha of arable land. No definite archaeological responses have been detected. Several anomalies of uncertain origin have been identified; these could be archaeological, agricultural or natural in origin. The remaining responses include underground pipes and cables, agricultural effects and areas of natural magnetic variation.

2 INTRODUCTION

2.1 Background synopsis

SUMO Services Ltd were commissioned to undertake a geophysical survey of an area outlined for residential development. This survey forms part of an archaeological investigation being undertaken by **Persimmon Homes**.

2.2 Site details

NGR / Postcode TG 503 132 / NR30 5SH

Location The site is located to the west of Caister-on-Sea, Norfolk. Jack Chase

Way forms the eastern boundary of the site, Norwich Road the south,

with agricultural land to the north and west.

HER/SMR Norfolk

District Great Yarmouth
Parish West Caister CP

Topography Flat

Current Land Use Arable

Weather Sunny, dry

Geology Solid: Crag Group - sand and gravel. Superficial: Lowestoft Formation -

diamicton is recorded across the southern field, with Happisburgh

Glacigenic Formation - sand across the north (BGS 2017).

Soils Wick 2 Association (541s) - deep, well drained, coarse loamy soils

(SSEW 1983).

Archaeology A search of Norfolk HER (2017) within a 1km radius of the site has

identified several archaeological records. Immediately south of Norwich Road, a Roman coin (NHER11657) and Neolithic axehead (NHER12311) have been discovered, along with a Roman enclosure and pits (NHER12737). Approximately 1km to the north-east of the site, cropmarks of a possible Bronze Age field system are recorded (NHER12996), with possible ring ditches (NHER27572; 27573) visible c. 250m west of the site. In a similar location to the ring ditches, cropmarks of a possible later prehistoric enclosure complex (NHER27609) are also recorded. The site of a WWII aircraft crash (NHER27477) is recorded at the northern fringe of the survey area, and a WWII coastal gun battery (NHER27475) is located immediately west of the site at Nova Scotia

Farm.

Survey Methods Magnetometer survey (fluxgate gradiometer)

Study Area c.30ha

Job ref: 11741 Date: Oct 2017

2.3 Aims and Objectives

To locate and characterise any anomalies of possible archaeological interest within the study area.

3 METHODS, PROCESSING & PRESENTATION

3.1 Standards & Guidance

This report and all fieldwork have been conducted in accordance with the latest guidance documents issued by Historic England (EH 2008) (then English Heritage), the Chartered Institute for Archaeologists (ClfA 2014) and the European Archaeological Council (EAC 2016).

3.2 Survey methods

Detailed magnetic survey was chosen as an efficient and effective method of locating archaeological anomalies.

Technique	Instrument	Traverse Interval	Sample Interval
Magnetometer	Bartington Cart System	1.0m	0.125m

More information regarding this technique is included in Appendix A.

3.3 Data Processing

The following basic processing steps have been carried out on the data used in this report:

De-stripe; interpolate

3.4 Presentation of results and interpretation

The presentation of the results for each site involves a grey-scale plot of processed data. Magnetic anomalies are identified, interpreted and plotted onto the 'Interpretation' drawings. The minimally processed data are provided as a greyscale image in the Archive Data Folder with an XY trace plot in CAD format. A free viewer is available: https://viewer.autodesk.com

When interpreting the results, several factors are taken into consideration, including the nature of archaeological features being investigated and the local conditions at the site (geology, pedology, topography etc.). Anomalies are categorised by their potential origin. Where responses can be related to other existing evidence, the anomalies will be given specific categories, such as: *Abbey Wall* or *Roman Road*. Where the interpretation is based largely on the geophysical data, levels of confidence are implied, for example: *Probable*, or *Possible Archaeology*. The former is used for a confident interpretation, based on anomaly definition and/or other corroborative data such as cropmarks. Poor anomaly definition, a lack of clear patterns to the responses and an absence of other supporting data reduces confidence, hence the classification *Possible*.

4 RESULTS

4.1 Probable / Possible Archaeology

4.1.1 No magnetic responses have been recorded that could be interpreted as being of archaeological interest.

4.2 Uncertain

- 4.2.1 A small series of positive linear anomalies are visible in the south-west of the site. These could be associated with former trackways, possibly related to the prehistoric activity recorded to the west (NCC 2017); however, the strength of the responses makes further interpretation difficult. An agricultural origin is equally possible, hence the classification of *Uncertain Origin*.
- 4.2.2 Further weak linear and discrete responses are visible in the north of the area. They are isolated and form no coherent patterns, leading to their interpretation as being of *Uncertain Origin*. An agricultural or natural origin is the most likely explanation.

4.3 Former Field Boundary

4.3.1 Two weak linear anomalies are visible in the south of the site, both orientated approximately east-west. The responses are a result of former field boundaries, visible on historic mapping. The southernmost boundary is visible from 1885-1907, while the northernmost is visible from 1885-1957.

4.4 Agricultural – Ploughing, Land Drains

4.4.1 Weakly magnetic, closely spaced, parallel linear responses at the northern and southern boundaries are a result of modern ploughing.

4.5 Natural / Geological / Pedological / Topographic

4.5.1 Several discrete and amorphous areas of enhanced response are visible across the site.

These are likely to be of natural origin, and are typical of natural magnetic variations detected over sands and gravels.

4.6 Ferrous / Magnetic Disturbance

- 4.6.1 Strong bipolar linear anomalies have been detected in the north of the site. These relate to underground services, such as pipes and cables.
- 4.6.2 Ferrous responses and magnetic disturbance close to boundaries are due to adjacent fences and gates. Smaller scale ferrous anomalies ("iron spikes") are present throughout the data and their form is best illustrated in the XY trace plots. These responses are characteristic of small pieces of ferrous debris (or brick / tile) in the topsoil and are commonly assigned a modern origin. Only the most prominent of these are highlighted on the interpretation diagram.

Job ref: 11741 Date: Oct 2017

5 DATA APPRAISAL & CONFIDENCE ASSESSMENT

5.1 Historic England guidelines (EH 2008) Table 4 states that the average magnetic response on sands and gravels can be variable. Given that linear anomalies of uncertain origin have been detected, it can be determined that the survey has been effective.

6 CONCLUSION

6.1 The survey at Nova Scotia Farm has not revealed any responses of definite archaeological origin. Linear anomalies of uncertain origin could have an archaeological provenance, though an agricultural origin is equally likely. Several underground services are visible in the north of the site, with modern agricultural effects visible in both the north and south.

7 REFERENCES

BGS 2017	British Geological Survey, Geology of Britain viewer [Accessed 04/10/2017] website: (http://www.bgs.ac.uk/opengeoscience/home.html?Accordion1=1#maps)
ClfA 2014	Standard and Guidance for Archaeological Geophysical Survey. Amended 2016. ClfA Guidance note. Chartered Institute for Archaeologists, Reading http://www.archaeologists.net/sites/default/files/ClfAS%26GGeophysics_2.pdf
EAC 2016	EAC Guidelines for the Use of Geophysics in Archaeology, European Archaeological Council, Guidelines 2.
EH 2008	Geophysical Survey in Archaeological Field Evaluation. English Heritage, Swindon https://content.historicengland.org.uk/images-books/publications/geophysical-survey-in-archaeological-field-evaluation/geophysics-guidelines.pdf/
NCC 2017	Norfolk County Council. <i>Historic Environment Record</i> [Accessed 04/10/2017] website: www.heritagegateway.org.uk
SSEW 1983	Soils of England and Wales. Sheet 4, Eastern England. Soil Survey of England and Wales, Harpenden.

Appendix A - Technical Information: Magnetometer Survey Method

Grid Positioning

For hand held gradiometers the location of the survey grids has been plotted together with the referencing information. Grids were set out using a Trimble R8 Real Time Kinematic (RTK) VRS Now GNSS GPS system.

Every point that is recorded using the cart system is referenced using a Trimble R* RTK GNSS system. An RTK GPS (Real-time Kinematic Global Positioning System) can locate a point on the ground to a far greater accuracy than a standard GPS unit. A standard GPS suffers from errors created by satellite orbit errors, clock errors and atmospheric interference, resulting in an accuracy of 5m-10m. An RTK system uses a single base station receiver and a number of mobile units. The base station rebroadcasts the phase of the carrier it measured, and the mobile units compare their own phase measurements with those they received from the base station. This results in an accuracy of around 0.01m.

Technique	Instrument	Traverse Interval	Sample Interval
Magnetometer	Bartington Cart	1.0m	0.125m

Instrumentation: Bartington Cart

Bartington instruments operate in a gradiometer configuration which comprises fluxgate sensors mounted vertically, set 0.5m apart. The fluxgate gradiometer suppresses any diurnal or regional effects. The instruments are carried, or cart mounted, with the bottom sensor approximately 0.1-0.3m from the ground surface. At each survey station, the difference in the magnetic field between the two fluxgates is measured in nanoTesla (nT). The sensitivity of the instrument can be adjusted; for most archaeological surveys the most sensitive range (0.1nT) is used. Generally, features up to 1m deep may be detected by this method, though strongly magnetic objects may be visible at greater depths. The Bartington Cart can collect four lines of data per traverse with gradiometer units mounted laterally with a separation of 0.5m. The readings are logged consecutively into the data logger which in turn is daily down-loaded into a portable computer whilst on site. At the end of each site survey, data is transferred to the office for processing and presentation.

The Bartington magnetometer cart system collects data at 10Hz which approximates 0.125m.

The readings are logged consecutively into the data logger which in turn is daily down- loaded into a portable computer whilst on site. At the end of each site survey, data is transferred to the office for processing and presentation.

Data Processing

Zero Mean Traverse This process sets the background mean of each traverse within each grid to zero. The operation removes striping effects and edge discontinuities over the whole of the data set.

Step Correction (De-stagger)

When gradiometer data are collected in 'zig-zag' fashion, stepping errors can sometimes arise. These occur because of a slight difference in the speed of walking on the forward and reverse traverses. The result is a staggered effect in the data, which is particularly noticeable on linear anomalies. This process corrects these errors.

Display

Greyscale/ Colourscale Plot This format divides a given range of readings into a set number of classes. Each class is represented by a specific shade of grey, the intensity increasing with value. All values above the given range are allocated the same shade (maximum intensity); similarly, all values below the given range are represented by the minimum intensity shade. Similar plots can be produced in colour, either using a wide range of colours or by selecting two or three colours to represent positive and negative values. The assigned range (plotting levels) can be adjusted to emphasise different anomalies in the data-set.

Interpretation Categories

In certain circumstances (usually when there is corroborative evidence from desk-based or excavation data) very specific interpretations can be assigned to magnetic anomalies (for example, Roman Road, Wall, etc.) and where appropriate, such interpretations will be applied. The list below outlines the generic categories commonly used in the interpretation of the results.

Archaeology / Probable Archaeology

This term is used when the form, nature and pattern of the responses are clearly or very probably archaeological and /or if corroborative evidence is available. These anomalies, whilst considered anthropogenic, could be of any age.

Possible Archaeology These anomalies exhibit either weak signal strength and / or poor definition, or form incomplete archaeological patterns, thereby reducing the level of confidence in the interpretation. Although the archaeological interpretation is favoured, they may be the result of variable soil depth, plough damage or even aliasing as a result of data collection orientation.

Industrial / Burnt-Fired Strong magnetic anomalies that, due to their shape and form or the context in which they are found, suggest the presence of kilns, ovens, corn dryers, metalworking areas or hearths. It should be noted that in many instances modern ferrous material can produce similar magnetic anomalies.

Former Field & possible)

Anomalies that correspond to former boundaries indicated on historic mapping, or Boundary (probable which are clearly a continuation of existing land divisions. Possible denotes less confidence where the anomaly may not be shown on historic mapping but nevertheless the anomaly displays all the characteristics of a field boundary.

Ridge & Furrow Parallel linear anomalies whose broad spacing suggests ridge and furrow cultivation. In some cases, the response may be the result of more recent agricultural activity.

Agriculture (ploughing)

Land Drain

Parallel linear anomalies or trends with a narrower spacing, sometimes aligned with existing boundaries, indicating more recent cultivation regimes.

Weakly magnetic linear anomalies, quite often appearing in series forming parallel and herringbone patterns. Smaller drains may lead and empty into larger diameter pipes, which in turn usually lead to local streams and ponds. These are indicative

of clay fired land drains.

Natural These responses form clear patterns in geographical zones where natural

variations are known to produce significant magnetic distortions.

Magnetic Disturbance Broad zones of strong dipolar anomalies, commonly found in places where modern ferrous or fired materials (e.g. brick rubble) are present. They are presumed to be modern.

Service

Magnetically strong anomalies, usually forming linear features are indicative of ferrous pipes/cables. Sometimes other materials (e.g. pvc) or the fill of the trench can cause weaker magnetic responses which can be identified from their uniform

linearity.

This type of response is associated with ferrous material and may result from small **Ferrous**

> items in the topsoil, larger buried objects such as pipes, or above ground features such as fence lines or pylons. Ferrous responses are usually regarded as modern. Individual burnt stones, fired bricks or igneous rocks can produce responses

similar to ferrous material.

Uncertain Origin Anomalies which stand out from the background magnetic variation, yet whose

form and lack of patterning gives little clue as to their origin. Often the characteristics and distribution of the responses straddle the categories of Possible Archaeology / Natural or (in the case of linear responses) Possible Archaeology /

Agriculture; occasionally they are simply of an unusual form.

Where appropriate some anomalies will be further classified according to their form (positive or negative) and relative strength and coherence (trend: weak and poorly defined).

© SUMO Survey: Geophysics for Archaeology and Engineering

Appendix B - Technical Information: Magnetic Theory

Detailed magnetic survey can be used to effectively define areas of past human activity by mapping spatial variation and contrast in the magnetic properties of soil, subsoil and bedrock. Although the changes in the magnetic field resulting from differing features in the soil are usually weak, changes as small as 0.1 nanoTeslas (nT) in an overall field strength of 48,000 (nT), can be accurately detected.

Weakly magnetic iron minerals are always present within the soil and areas of enhancement relate to increases in *magnetic susceptibility* and permanently magnetised *thermoremanent* material.


Magnetic susceptibility relates to the induced magnetism of a material when in the presence of a magnetic field. This magnetism can be considered as effectively permanent as it exists within the Earth's magnetic field. Magnetic susceptibility can become enhanced due to burning and complex biological or fermentation processes.


Thermoremanence is a permanent magnetism acquired by iron minerals that, after heating to a specific temperature known as the Curie Point, are effectively demagnetised followed by re-magnetisation by the Earth's magnetic field on cooling. Thermoremanent archaeological features can include hearths and kilns; material such as brick and tile may be magnetised through the same process.


Silting and deliberate infilling of ditches and pits with magnetically enhanced soil creates a relative contrast against the much lower levels of magnetism within the subsoil into which the feature is cut. Systematic mapping of magnetic anomalies will produce linear and discrete areas of enhancement allowing assessment and characterisation of subsurface features. Material such as subsoil and non-magnetic bedrock used to create former earthworks and walls may be mapped as areas of lower enhancement compared to surrounding soils.


Magnetic survey is carried out using a fluxgate gradiometer which is a passive instrument consisting of two sensors mounted vertically 1m apart. The instrument is carried about 30cm above the ground surface and the top sensor measures the Earth's magnetic field whilst the lower sensor measures the same field but is also more affected by any localised buried feature. The difference between the two sensors will relate to the strength of a magnetic field created by this feature, if no field is present the difference will be close to zero as the magnetic field measured by both sensors will be the same.


Factors affecting the magnetic survey may include soil type, local geology, previous human activity and disturbance from modern services.











- Archaeological
- Geophysical
- Laser Scanning
- Measured Building
- Topographic
- Utility Mapping