

GEOPHYSICAL SURVEY REPORT

STRATASCAN™



Project name:
Eastleigh, Hampshire

Client:
CFA Archaeology

Job ref:
J10045

June 2016

GEOPHYSICAL SURVEY REPORT

| | |
|---|---|
| Project name: Eastleigh, Hampshire Client: CFA Archaeology | Job ref: J10045 |
| Survey date: 16th June 2016 | Report date: June 2016 |
| Field team: Thomas Hynd BSc (Hons) Alexis Thouki MA Mark Goddard BA (Hons) Edwin Pearson PgCert | Project Manager: Simon Haddrell BEng(Hons) AMBCS PCIfA |
| Report written by: Rebecca Davies BSc (Hons) | Report approved by: Peter Barker CEng MICE MCIWEM MCIfA FCInstCES |
| CAD illustrations by: Rebecca Davies BSc (Hons) | Site Director: Peter Barker CEng MICE MCIWEM MCIfA FCInstCES |
| Version number and issue date: V1 29/06/2016 | Amendments: |



STRATASCAN LTD
Vineyard House Upper Hook Road Upton upon Severn
Worcestershire WR8 0SA United Kingdom

T: 01684 592266 F: 01684 594142
info@stratascansumo.com www.stratascan.co.uk

TABLE OF CONTENTS

| | | |
|----------|--|----------|
| 1 | SUMMARY OF RESULTS..... | 1 |
| 2 | INTRODUCTION | 1 |
| 3 | METHODS, PROCESSING & PRESENTATION..... | 3 |
| 4 | RESULTS | 4 |
| 5 | DATA APPRAISAL & CONFIDENCE ASSESSMENT | 5 |
| 6 | CONCLUSION | 5 |
| 7 | REFERENCES | 6 |
| | Appendix A - Technical Information: Magnetometer Survey Method..... | 7 |
| | Appendix B - Technical Information: Magnetic Theory | 9 |

LIST OF FIGURES

| | | |
|-----------|----------|--|
| Figure 01 | 1:25 000 | Location plan of survey area |
| Figure 02 | 1:2000 | Location of survey grids and referencing |
| Figure 03 | 1:2000 | Colour plot of gradiometer data showing extreme values – overview |
| Figure 04 | 1:1000 | Colour plot of gradiometer data showing extreme values – north west |
| Figure 05 | 1:1000 | Colour plot of gradiometer data showing extreme values – south east |
| Figure 06 | 1:2000 | Plot of minimally processed gradiometer data – overview |
| Figure 07 | 1:1000 | Plot of minimally processed gradiometer data – north west |
| Figure 08 | 1:1000 | Plot of minimally processed gradiometer data – south east |
| Figure 09 | 1:2000 | Abstraction and interpretation of gradiometer anomalies – overview |
| Figure 10 | 1:1000 | Abstraction and interpretation of gradiometer anomalies – north west |
| Figure 11 | 1:1000 | Abstraction and interpretation of gradiometer anomalies – south east |
| Figure 12 | 1:2000 | Gradiometer interpretation with known services |

1 SUMMARY OF RESULTS

A detailed gradiometry survey was conducted over approximately 4.3 hectares of arable farmland and pasture. No features of probable or possible archaeological origin have been identified. A former field boundary or trackway indicates that the site has a recent agricultural past. The remaining features are modern and include underground services, areas of scattered magnetic debris, disturbance from substantial nearby ferrous objects, and magnetic spikes which are likely to be modern rubbish.

2 INTRODUCTION

2.1 Background synopsis

Stratascan were commissioned to undertake a geophysical survey of an area outlined for the development of an Energy Recovery Centre, comprising pyrolysis and an anaerobic digestion plant, and a commercial solar farm. This survey forms part of an archaeological investigation being undertaken by CFA Archaeology.

2.2 Site Details

| | |
|-------------------------|--|
| NGR / Postcode | SU 465 179 / SO50 6RQ |
| Location | The site is located at the south-east of Eastleigh, Hampshire. The site is bound by a railway line to the south, water meadows to the east, the Southern Water Wastewater Treatment works to the north and an industrial estate to the west. |
| HER/SMR | Hampshire |
| District | Eastleigh |
| District Ward | Eastleigh Central |
| Topography | Relatively flat |
| Current Land Use | Arable in the west and pasture in the east. |
| Soils | The overlying soils are unsurveyed, mainly urban and industrial areas (Soil Survey of England and Wales, Sheet 6 South East England). |
| Geology | The underlying geology comprises Wittering Formation – sand, silt and clay. The drift geology comprises River Terrace Deposits, 1 - clay and silt (British Geological Survey website). |

| | |
|------------------------------|---|
| <p>Archaeology</p> | <p>The following is taken from “ERC & Solar Farm, Chicken Hall Lane, Eastleigh – Heritage Desk Based Assessment” (Waterman, 2013):</p> <p><i>There are two prehistoric assets recorded within the 1km search area, namely a Neolithic chipped celt (axe) “found at Bishopstoke in 1905” and an early Bronze Age small socketed spear head “found near the river at Bishopstoke” (25906 and 25917 respectively).</i></p> <p><i>There are a number of finds dating to the Roman period within the 1km search area, including the site of a possible Roman Villa (25907), approximately 300m to the north of the Site. This was first recorded on the 1908 Ordnance Survey map 62 and currently lies beneath sludge beds within the Sewage Works which abut the Site to the north. A small bronze coin (25910) of Claudius Gothicus (AD268-269) was found near the possible Roman villa and coffin (mapped in the HER within the perimeter of the sewage works). A jar containing c. 200 Roman coins (25901) was found in 1878 in the ballast field at Bishopstoke with several other Roman artefacts, including 15 Roman pottery vessels (25900), reportedly in a huge trench containing horse’s heads and grain.</i></p> <p><i>The discovery of Roman remains is not surprising due to the proximity of a Roman road between Winchester (Venta Belgarum) and Southampton (Clausentum), which passes through Eastleigh, approximately 2.4 km from the west boundary of the Site.</i></p> <p><i>There are no finds dating from the early medieval period within the 1km search radius, although routeways dating from the middle Saxon period can be traced linking Stoneham Common with the town of Hamwic, and with the ‘west landing place’ on the Itchen (probably near Chickenhall Farm and North Stoneham Farms). Close association of these latter settlements with two known sites of Roman buildings may suggest even longer continuity.</i></p> <p><i>The HER records several entries for medieval / post-medieval field systems, evidenced by linear features visible as cropmarks in aerial photographs, namely 58288 to the south-west of the Site, and 58291, as part of a desk-based review of aerial photography for the area.</i></p> |
| <p>Survey Methods</p> | <p>Detailed magnetic survey (gradiometry)</p> |
| <p>Study Area</p> | <p>c.5.3 hectares – approximately 1 hectare could not be surveyed due to overgrown vegetation reducing the survey area to c. 4.3 hectares.</p> |

2.3 Aims and objectives

To locate and characterise any anomalies of possible archaeological interest within the study area.

3 METHODS, PROCESSING & PRESENTATION

3.1 Standards & Guidance

This report and all fieldwork have been conducted in accordance with the latest guidance documents issued by Historic England (2008) and the Chartered Institute for Archaeologists (2002 & 2014).

Stratascan Ltd are a Registered Organisation with the Cifa and are committed to upholding its policies and standards.

3.2 Survey methods

Due to the moderate potential for Roman remains, detailed magnetic survey was used as an efficient and effective method of locating archaeological anomalies.

More information regarding this technique is included in Appendix A.

3.3 Processing

The following schedule shows the basic processing carried out on the data used in this report:

1. *Destripe*
2. *Destagger*

3.4 Presentation of results and interpretation

The presentation of the data for each site involves a plot of the minimally processed data as a greyscale plot and a colour plot showing extreme magnetic values. Magnetic anomalies have been identified and plotted onto the 'Interpretation of Anomalies' drawing.

When interpreting the results several factors are taken into consideration, including the nature of archaeological features being investigated and the local conditions at the site (geology, pedology, topography etc.). Anomalies are categorised by their potential origin. Where responses can be related to very specific known features documented in other sources, this is done (for example: Abbey Wall, Roman Road). For the generic categories levels of confidence are indicated, for example: probable, or possible archaeology. The former is used for a confident interpretation, based on anomaly definition and/or other corroborative data such as cropmarks. Poor anomaly definition, a lack of clear patterns to the responses and an absence of other supporting data reduces confidence, hence the classification "possible".

4 RESULTS

The detailed magnetic gradiometer survey conducted at Eastleigh has not identified any anomalies that have been characterised as being either of a *probable* or *possible* archaeological origin. The following refers to numerical labels on the interpretation plots.

4.1 *Probable Archaeology*

No probable archaeology has been identified within the survey area.

4.2 *Possible Archaeology*

No possible archaeology has been identified within the survey area.

4.3 *Medieval/Post-Medieval Agriculture*

A single, positive linear anomaly [1] in the west of the site is related to former field boundary or trackway, visible on available historic OS mapping from 1872 to 1946.

4.4 *Other Anomalies*

A number of strong, bipolar linear anomalies across the site [2] are related to underground services such as pipes or cables. Three of the services identified correlate with the approximate locations of sewers and a pumping main (Fig.12), however some of the services are previously undetected. A positive linear anomaly [3] is related to a 375mm sewer (Fig 12). Large areas of scattered magnetic debris [4], predominantly in the south of the site, are likely to be modern in origin and relate to recently deposited rubbish. Areas of magnetic disturbance [5] are the result of substantial nearby ferrous metal objects, such as services and fencing, Smaller ferrous anomalies, or 'magnetic spikes' [6] indicate ferrous metal objects and are likely to be modern rubbish.

5 DATA APPRAISAL & CONFIDENCE ASSESSMENT

Underlying geologies of sand, silt and clay can provide variable results for gradiometer survey. The site is largely dominated by areas of moderate strength magnetic debris and disturbance from underground services. The effects of both the debris and disturbance has the potential to mask weaker archaeological anomalies. In the areas not affected by the debris and disturbance, a former field boundary has been identified, and it is likely that any archaeological anomalies, lying outside of the areas of disturbance, would have been detected.

6 CONCLUSION

The survey at Eastleigh has not identified any features of probable or possible archaeological origin, despite the potential for Roman remains outlined in the desk-based assessment of the site. A former field boundary or trackway, visible on available historic mapping, indicates that the site has a recent agricultural past. The remaining features are modern and include underground services and a service trench, likely associated with the nearby Southern Water Wastewater Treatment works, areas of scattered magnetic debris, disturbance from substantial nearby ferrous objects, and magnetic spikes which are likely to be modern rubbish.

7 REFERENCES

British Geological Survey, n.d., *website*:
(<http://www.bgs.ac.uk/opengeoscience/home.html?Accordion1=1#maps>) Geology of Britain viewer. [Accessed 11/01/2015]

Chartered Institute For Archaeologists. *Standard and Guidance for Archaeological Geophysical Survey*. (http://www.archaeologists.net/sites/default/files/CIfAS&GGeophysics_1.pdf)

English Heritage, 2008. *Geophysical Survey in Archaeological Field Evaluation*.

IfA 2002. The Use of Geophysical Techniques in Archaeological Evaluations, IFA Paper No 6, C. Gaffney, J. Gater and S. Ovenden. Institute for Archaeology, Reading

Soil Survey of England and Wales, 1983. *Soils of England and Wales, Sheet 6 South East England*

Waterman Energy, Environment & Design Limited, 2013. *ERC & Solar Farm, Chicken Hall Lane, Eastleigh – Heritage Desk Based Assessment*

Appendix A - Technical Information: Magnetometer Survey Method

Grid Positioning

For hand held gradiometers the location of the survey grids has been plotted together with the referencing information. Grids were set out using a Trimble R8 Real Time Kinematic (RTK) VRS Now GNSS GPS system.

An RTK GPS (Real-time Kinematic Global Positioning System) can locate a point on the ground to a far greater accuracy than a standard GPS unit. A standard GPS suffers from errors created by satellite orbit errors, clock errors and atmospheric interference, resulting in an accuracy of 5m-10m. An RTK system uses a single base station receiver and a number of mobile units. The base station re-broadcasts the phase of the carrier it measured, and the mobile units compare their own phase measurements with those they received from the base station. This results in an accuracy of around 0.01m.

| Technique | Instrument | Traverse Interval | Sample Interval |
|--------------|-----------------------|-------------------|-----------------|
| Magnetometer | Bartington Grad 601-2 | 1m | 0.25m |

Instrumentation: Bartington *Grad601-2*

Bartington instruments operate in a gradiometer configuration which comprises fluxgate sensors mounted vertically, set 1.0m apart. The fluxgate gradiometer suppresses any diurnal or regional effects. The instruments are carried, or cart mounted, with the bottom sensor approximately 0.1-0.3m from the ground surface. At each survey station, the difference in the magnetic field between the two fluxgates is measured in nanoTesla (nT). The sensitivity of the instrument can be adjusted; for most archaeological surveys the most sensitive range (0.1nT) is used. Generally, features up to 1m deep may be detected by this method, though strongly magnetic objects may be visible at greater depths. The Bartington instrument can collect two lines of data per traverse with gradiometer units mounted laterally with a separation of 1.0m.

The readings are logged consecutively into the data logger which in turn is daily down-loaded into a portable computer whilst on site. At the end of each site survey, data is transferred to the office for processing and presentation.

Data Processing

Zero Mean Traverse This process sets the background mean of each traverse within each grid to zero. The operation removes striping effects and edge discontinuities over the whole of the data set.

Step Correction (Destagger) When gradiometer data are collected in 'zig-zag' fashion, stepping errors can sometimes arise. These occur because of a slight difference in the speed of walking on the forward and reverse traverses. The result is a staggered effect in the data, which is particularly noticeable on linear anomalies. This process corrects these errors.

Display

Greyscale/ Colourscale Plot This format divides a given range of readings into a set number of classes. Each class is represented by a specific shade of grey, the intensity increasing with value. All values above the given range are allocated the same shade (maximum intensity); similarly all values below the given range are represented by the minimum intensity shade. Similar plots can be produced in colour, either using a wide range of colours or by selecting two or three colours to represent positive and negative values. The assigned range (plotting levels) can be adjusted to emphasise different anomalies in the data-set.

Interpretation Categories

In certain circumstances (usually when there is corroborative evidence from desk based or excavation data) very specific interpretations can be assigned to magnetic anomalies (for example, *Roman Road, Wall*, etc.) and where appropriate, such interpretations will be applied. The list below outlines the generic categories commonly used in the interpretation of the results.

| | |
|--|--|
| <i>Archaeology/Probable Archaeology</i> | This term is used when the form, nature and pattern of the response are clearly or very probably archaeological and /or if corroborative evidence is available. These anomalies, whilst considered anthropogenic, could be of any age. |
| <i>Possible Archaeology</i> | These anomalies exhibit either weak signal strength and / or poor definition, or form incomplete archaeological patterns, thereby reducing the level of confidence in the interpretation. Although the archaeological interpretation is favoured, they may be the result of variable soil depth, plough damage or even aliasing as a result of data collection orientation. |
| <i>Industrial / Burnt-Fired</i> | Strong magnetic anomalies that, due to their shape and form or the context in which they are found, suggest the presence of kilns, ovens, corn dryers, metal-working areas or hearths. It should be noted that in many instances modern ferrous material can produce similar magnetic anomalies. |
| <i>Former Field Boundary (probable & possible)</i> | Anomalies that correspond to former boundaries indicated on historic mapping, or which are clearly a continuation of existing land divisions. Possible denotes less confidence where the anomaly may not be shown on historic mapping but nevertheless the anomaly displays all the characteristics of a field boundary. |
| <i>Ridge & Furrow</i> | Parallel linear anomalies whose broad spacing suggests ridge and furrow cultivation. In some cases the response may be the result of more recent agricultural activity. |
| <i>Agriculture (ploughing)</i> | Parallel linear anomalies or trends with a narrower spacing, sometimes aligned with existing boundaries, indicating more recent cultivation regimes. |
| <i>Land Drain</i> | Weakly magnetic linear anomalies, quite often appearing in series forming parallel and herringbone patterns. Smaller drains will often lead and empty into larger diameter pipes and which in turn usually lead to local streams and ponds. These are indicative of clay fired land drains. |
| <i>Natural</i> | These responses form clear patterns in geographical zones where natural variations are known to produce significant magnetic distortions. |
| <i>Magnetic Disturbance</i> | Broad zones of strong dipolar anomalies, commonly found in places where modern ferrous or fired materials (e.g. brick rubble) are present. They are presumed to be modern. |
| <i>Service</i> | Magnetically strong anomalies usually forming linear features indicative of ferrous pipes/cables. Sometimes other materials (e.g. pvc) cause weaker magnetic responses and can be identified from their uniform linearity crossing large expanses. |
| <i>Ferrous</i> | This type of response is associated with ferrous material and may result from small items in the topsoil, larger buried objects such as pipes, or above ground features such as fence lines or pylons. Ferrous responses are usually regarded as modern. Individual burnt stones, fired bricks or igneous rocks can produce responses similar to ferrous material. |
| <i>Uncertain Origin</i> | Anomalies which stand out from the background magnetic variation, yet whose form and lack of patterning gives little clue as to their origin. Often the characteristics and distribution of the responses straddle the categories of <i>Possible Archaeology</i> and <i>Possible Natural</i> or (in the case of linear responses) <i>Possible Archaeology</i> and <i>Possible Agriculture</i> ; occasionally they are simply of an unusual form. |

Where appropriate some anomalies will be further classified according to their form (positive or negative) and relative strength and coherence (trend: weak and poorly defined).

Appendix B - Technical Information: Magnetic Theory

Detailed magnetic survey can be used to effectively define areas of past human activity by mapping spatial variation and contrast in the magnetic properties of soil, subsoil and bedrock. Although the changes in the magnetic field resulting from differing features in the soil are usually weak, changes as small as 0.2 nanoTeslas (nT) in an overall field strength of 48,000nT, can be accurately detected.

Weakly magnetic iron minerals are always present within the soil and areas of enhancement relate to increases in *magnetic susceptibility* and permanently magnetised *thermoremanent* material.

Magnetic susceptibility relates to the induced magnetism of a material when in the presence of a magnetic field. This magnetism can be considered as effectively permanent as it exists within the Earth's magnetic field. Magnetic susceptibility can become enhanced due to burning and complex biological or fermentation processes.

Thermoremanence is a permanent magnetism acquired by iron minerals that, after heating to a specific temperature known as the Curie Point, are effectively demagnetised followed by re-magnetisation by the Earth's magnetic field on cooling. Thermoremanent archaeological features can include hearths and kilns and material such as brick and tile may be magnetised through the same process.

Silting and deliberate infilling of ditches and pits with magnetically enhanced soil creates a relative contrast against the much lower levels of magnetism within the subsoil into which the feature is cut. Systematic mapping of magnetic anomalies will produce linear and discrete areas of enhancement allowing assessment and characterisation of subsurface features. Material such as subsoil and non-magnetic bedrock used to create former earthworks and walls may be mapped as areas of lower enhancement compared to surrounding soils.

Magnetic survey is carried out using a fluxgate gradiometer which is a passive instrument consisting of two sensors mounted vertically 1m apart. The instrument is carried about 30cm above the ground surface and the top sensor measures the Earth's magnetic field whilst the lower sensor measures the same field but is also more affected by any localised buried field. The difference between the two sensors will relate to the strength of a magnetic field created by a buried feature, if no field is present the difference will be close to zero as the magnetic field measured by both sensors will be the same.

Factors affecting the magnetic survey may include soil type, local geology, previous human activity, disturbance from modern services etc.

Survey services you can rely on

Your Survey Partner

For a complete and complementary range of survey services.

*Survey services
you can rely on*

- Archaeological
- As Built Records
- Boundary Disputes
- CCTV
- Geophysical
- Laser Scanning
- Measured Building
- Pipeline Routes
- Railway
- Retrofit
- Setting Out
- Statutory Plan Collation
- Topographic
- Utility Mapping
- UXO Detection
- Void Detection

